

X1-X1600 / X3-X1800

I3200-A1

I3200-E1



Mode	X1-X1600-I3200A1 / X3-X1800-I3200A1	X1-X1600-I3200E1 / X3-X1800-I3200E1
Printing Speed/Mode	3PASS:30m ² /h 4PASS:22m ² /h 6PASS:15m ² /h	3PASS:30m ² /h 4PASS:22m ² /h 6PASS:15m ² /h I3200-E1 1pc

PRODUCT FEATURES

- I3200-A1、I3200-E1
 - Optional I3200-A1/I3200-E1 printhead;
 - Constant tension feeding and take up system, materials feeding and take up more accurate and stable;
 - Standard front, middle heater, optional with drying lamp and fans system;
 - Complete machine mature printing system, stable mechanical

SPECIFICATIONS

Print Width	X1-X1600: 1.52M X3-X1800: 1.8M	Media Type	All kinds of indoor and outdoor advertising materials and decoration materials
Heating System	Standard with front infrared dryer	Dimensions(mm)	X1-X1600: L2362*W900*H1500mm X3-X1800: L2621*W900*H1500mm
Temperature/Humidity	: 20-30°C.; 45-65% Temperature: 20-30°C, Humidity: 45-65%	Packing Dimensions(mm)	X1-X1600: L2440*W710*H660mm X3-X1800: L2730*W710*H710mm
Power	800W,; 1200W Machine Power: 800W External drying: 1200W	Net Weight(KG)	X1-X1600: 152KG X3-X1800: 166KG
RIP Software	/Photoprint Maintop / Photoprint (Optional)	(KG) Gross Weight(KG)	X1-X1600: 220KG X3-X1800: 240KG